

Product data sheet

Closer body TS 550 NV

F



Basic body for floor-mounted door closer EN 3-6 without
hold-open function

AREAS OF APPLICATION

- Right and left single-action doors
- Single-action doors up to 1400 mm leaf width
- For leaf weights up to 300 kg

Closer body TS 550 NV F



PRODUCT FEATURES

- Closing force with variable adjustment
- Closing speed can be adjusted from the top via valves
- Latching action can be adjusted from the top via valves
- Back check can be adjusted from the top via valves
- Delayed closing can be adjusted from the top via valve
- Door closer, can be used for right and left hand doors

TECHNICAL DATA

Productname	Closer body TS 550 NV F
Suitability for fire protection doors	Yes
Use on single-/double-action door	Single-action door
Opening angle (max.)	180 °
Closing force in accordance with EN 1154	EN 3 - 6
Leaf width (max.)	1400 mm
Leaf weight (max.)	300 kg
DIN direction	left / right
Standard conformity	EN 1154:1996/A1:2002/AC:2006
Length	342 mm
Width	82 mm
Height	54 mm
Length adjustment range for cement box	9 mm
Width adjustment range for cement box	10 mm
Height adjustment range for cement box	6 mm
Closing force adjustable	Yes, stepless
Adjustable closing speed	Yes
Latching action adjustable	Yes, via valve
Back check integrated	Mechanically fixed
Delayed closing integrated	Yes
Position of closing force adjustment	Top
Safety valve against overload	Yes
Thermo-control valves	Yes
Closing effect from	180 °
Hold-open of fire protection doors	No

Closer body TS 550 NV F



VARIANTS / ORDER INFO

Designation	Description	Ident- No.	Closing force in accordance with EN 1154	Dimension s	DIN direction
GEZE TS 550 NV F Closer	Size EN 3-6, closing effect from 180°, without hold-open device, delayed closing possible, door leaf weight up to 300 kg (without cover plate and accessories)	132755	EN 3 - 6	342 x 82 x 54 mm	left
GEZE TS 550 NV F Closer	Size EN 3-6, closing effect from 180°, without hold-open device, delayed closing possible, door leaf weight up to 300 kg (without cover plate and accessories)	132754	EN 3 - 6	342 x 82 x 54 mm	right