

Product data sheet WTH *



Remote control for activating GEZE automatic doors and window drives via the GEZE wireless programme

AREAS OF APPLICATION

- ightarrow Activation of GEZE automatic doors and window drives via the GEZE wireless program
- → Activation of smoke and heat extraction systems
- → Components can be activated wirelessly in a system concept individually, together, or in groups





PRODUCT FEATURES

- → Combined activation of doors and windows using a remote control
- → Encrypted communication via rolling code with up to 74 trillion code combinations
- → Custom and reliable teach-in to exclude unauthorised activation
- → Available in 1, 2, or 4 channel versions
- → Doors can be controlled over great distances even through walls
- ightarrow With two outputs to which individual radio receivers can be taught in
- → Integrated dip switch for selecting different modes of operation, e.g. press the button briefly for "open door" and press button longer for "hold door open"
- → LED function indicator for battery and transmission check
- → Radio range up to 30 m inside the building

TECHNICAL DATA

Productname	WTH *
Dimensions	78 x 51 x 15 mm
Operating current	45 mA
IP rating	IP54
Type of installation	Wall
Transmission frequency	433.93 Mhz
Service temperature	0 - 50 °C

VARIANTS / ORDER INFO

Designation

WTH-2 remote control, 2 channel *
WTH-4 remote control, 4 channel *
WTH-1 remote control, 1 channel *

^{*} The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.