

# Product data sheet

# **Levolan 120 glass**

# **fanlight attachment**



Sliding door fitting for 120 kg glass leafs and fanlight attachment

# Levolan 120 glass fanlight attachment



## AREAS OF APPLICATION

- For design-oriented interior sliding doors for living and office areas
- For all single- and multiple-leaf sliding doors
- Attachment directly to glass
- For attachment on the wall and ceiling (directly and concealed) as well as for glass installation
- Damped on one or both sides with Levolan 120 SoftStop
- Smooth running with Levolan 120 SoftStop makes it particularly well suited for doors in living and office spaces

## PRODUCT FEATURES

- Sliding door fitting for glass doors up to 120 kg leaf weight and direct attachment to glass walls or fanlights
- With damping on one or both sides, for doors up to 120 kg leaf weight so that the door is stopped gently and pulled autonomously into the end position
- Small floor and side profiles create a generous clearance gauge for fixed panels and glass sliding doors
- Fixed glass panels can be installed quickly and easily with rubber seals
- Modular fixed panel option as an "add-on" for the basic hardware

## TECHNICAL DATA

Productname	Levolan 120 glass fanlight attachment
-------------	---------------------------------------

## PART

### LSG GLASS / METAL GLUE \*

Glass metal glueing kit for connecting aluminium brackets with glass panes



Designation	Description	Ident-No.
LSG glass / metal glue 50 g *	for up to 30 sliding panels	133039

# Levolan 120 glass fanlight attachment



## LEVOLAN 120 COMPLETE SET

Levolan sliding door fitting for leaf weights up to 120 kg



Designation	Description	Ident-No.	Colour	Leaf width (min.)	Leaf width (max.)
Levolan 120 complete set	For wall installation	157943	Stainless steel optic	640 mm	1240 mm
Levolan 120 complete set	For wall installation	157940	EV1	640 mm	1440 mm
Levolan 120 complete set	For wall installation	157944	Stainless steel optic	640 mm	1440 mm
Levolan 120 complete set	For wall installation	157939	EV1	640 mm	1240 mm

## ACCESSORIES

### SPACER PROFILE FOR WALL CLEARANCE LEVOLAN 60 / 120

Spacer profile for wall installation of Levolan 60/120



Designation	Description	Ident-No.	Colour
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	157993	Stainless steel optic
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147571	Stainless steel optic
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147557	EV1
Spacer profile for wall clearance Levolan 60 / 120 *	10 mm additional space, can be stacked up to 20 mm	147559	Stainless steel optic
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147572	Stainless steel optic
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147558	EV1
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm / bespoke configuration	147573	
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	157991	EV1
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147560	Stainless steel optic
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147556	EV1
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147555	EV1

# Levolan 120 glass fanlight attachment



## LEVOLAN 120 SOFTSTOP SET, DAMPED ON ONE SIDE, UP TO 120 KG

Levolan SoftStop draw-in damping on one side left version



Designation	Description	Ident-No.	Leaf width (min.)	Leaf width (max.)
Levolan 120 SoftStop set, damped on one side, up to 120 kg	for draw-in damping left, consisting of: 1 x damping unit, 2 x spacers for cover panel bracket, 1 x trigger, can also be retrofitted – minimum leaf width on one side 900 mm, on both sides 1,325 mm	157999	900 mm	1440 mm

\* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.