

Product data sheet Perlan 140 glass with 30 mm glass clamping plate wall installation



Sliding door fitting system for glass doors with 80 kg leaf weight and 30 mm glass clamping plate and wall installation

AREAS OF APPLICATION

- ightarrow Frequently used interior sliding doors
- ightarrow Living, office, and conference areas as well as hotels
- ightarrow Installation of fittings in all visible areas
- ightarrow Single and multiple-leaf sliding doors
- ightarrow Installation in front of the wall

Product data sheet | Page 2 of 8 Perlan 140 glass with 30 mm glass clamping plate wall installation



PRODUCT FEATURES

- ightarrow Sliding door fitting for leaf weights up to 80 kg
- ightarrow For glass leaves with a 30 mm glass clamping plate
- \rightarrow With damping on one or both sides for doors with up to 80 kg leaf weight, so that the door is quietly slowed down and moved into the end position
- ightarrow Adjustable wall brackets balance out uneven masonry and allow for a freely selectable clearance from the wall
- ightarrow Precision ball bearings in the roller carriages offer very smooth sliding action
- ightarrow Tested for durability in accordance with DIN EN 1527 over 100,000 test cycles

TECHNICAL DATA

Productname

Perlan 140 glass with 30 mm glass clamping plate wall installation

PART

TRACK PERLAN 140

Track for sliding door fitting



Designation	Description	Ident-No.	Colour
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	142518	EV1
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	128660	EV1
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	128662	Stainless steel optic
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	135048	EV1
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	135047	EV1
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	142519	EV1
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	135046	EV1

FLOOR GUIDE FOR GLASS LEAF

Floor guide with variable adjustment for glass thicknesses 8, 10 and 12 $\,\rm mm$

Designation	Description	ldent- No.	Colour	Glass thickness
Floor guide for glass leaf (adjustable)	with variable adjustment for glass thickness 8-13.5 mm, with frieze band for noise reduction with structured glass surfaces, without attachment material	120417	silver- coloured	8 - 13.5 mm

SET CAPS FOR GLASS CLAMPING PLATE 30 MM *

End cap for glass clamping plate 30, set comprising 2 pieces

Designation	Description	ldent- No.	Glass thickness
Set caps for glass clamping plate 30 mm	2 caps for installation on the outer leaf side for attachment of the continuous cover and side caps, necessary where the cover panel projects > 200 mm beyond the glass clamping plate	142373	8 - 12 mm

GLASS CLAMPING PLATE 30 MM SET, CONTINUOUSLY BLENDED

Glass clamping plate 30 for leaf weights up to 80 kg with continuous cover panels











Perlan 140 glass with 30 mm glass clamping plate wall installation

GLASS CLAMPING PLATE 30 MM SET, WITH COVERING

Glass clamping plate 30 mm including cover for leaf weights up to 80 kg

Designation	Description	ldent- No.	Colour	Glass thickness
Glass clamping plate 30 mm set, with covering	Consisting of 2 glass clamping plates incl. suspension bolts, individual cover profiles and end caps, up to 80 kg leaf weight, for 8–12 mm toughened safety glass	142366	Stainless steel optic	8 - 12 mm
Glass clamping plate 30 mm set, with covering	Consisting of 2 glass clamping plates incl. suspension bolts, individual cover profiles and end caps, up to 80 kg leaf weight, for 8–12 mm toughened safety glass	142367	according to RAL	8 - 12 mm
Glass clamping plate 30 mm set, with covering	Consisting of 2 glass clamping plates incl. suspension bolts, individual cover profiles and end caps, up to 80 kg leaf weight, for 8-12 mm toughened safety glass	142365	EV1	8 - 12 mm

GLASS CLAMPING PLATE 30 MM SET, WITHOUT COVER

Glass clamping plate 30 for leaf weights up to 80 kg without cover

0 0.750 0

Designation	Description	ldent- No.	Glass thickness
Glass clamping plate 30 mm set, without cover	Consisting of 2 glass clamping plates incl. suspension bolts, up to 80 kg leaf weight, for 8–12 mm toughened safety glass	142364	8 - 12 mm

ACCESSORIES

END STOP WITH ADJUSTABLE HOLD-OPEN SPRING

Adjustable end stop for Perlan sliding door fitting

Designation

End stop with adjustable hold-open spring









069274

HOLD-OPEN SPRING

clamping plate wall installation

Hold-open spring for Perlan 140 end stop

Designation	Ident-No.
Hold-open spring	064242

DOOR STOP

Designation

mm

Clamping insert, glass clamping plate 30

End stop for sliding leaves

Designation	Ident-No.
Door stop	000339
Door stop	000342

LSG GLASS / METAL GLUE *

Glass metal glueing kit for connecting aluminium brackets with glass panes

Designation	Description	Ident-No.
LSG glass / metal glue 50 g *	for up to 30 sliding panels	133039

CLAMPING INSERT, GLASS CLAMPING PLATE 30 MM *

Description

glass

Clamping shim for glass thicknesses of 12.76 mm (1/2 inch)

for 2 glass clamping plates, for use with 12.7 mm (1/2 inch) toughened safety









Ident-No.

142634





Q()

PERLAN SOFTSTOP SET, MEDIUM VERSION, DAMPED ON ONE SIDE, UP TO 80 KG

Perlan SoftStop damping on one side for leaf weights up to 80 kg and leaf widths of 900 up to 1290 $\rm mm$

Designation	Description	ldent- No.	Leaf width (min.)	Leaf width (max.)
Perlan SoftStop set, medium, one side	The set includes: 2 x roller carriage with damping unit on one side, 2 x end stop, 1 x trigger with fixing screw, 2 x standard suspension plate	128877	900 mm	1290 mm

PERLAN SOFTSTOP SET, LONG VERSION, DAMPED ON BOTH SIDES, UP TO 80 KG

Perlan SoftStop damping on both sides for leaf weights up to 80 kg



SET PERLAN SOFTSTOPDUO, DAMPED ON BOTH SIDES

Perlan SoftStopDuo with damping on both sides up to 80 kg leaf weight



Designation	Description	ldent- No.	Leaf width (min.)	Leaf width (max.)
Perlan SoftStopDuo set, damped on both sides, up to 80 kg	The set includes: 2 x roller carriage with damping unit on both sides, 2 x end stop, 2 x trigger with fixing screws, 2 x standard suspension plate	150071	750 mm	1290 mm

Product data sheet | Page 7 of 8 Perlan 140 glass with 30 mm glass clamping plate wall installation

LSG GLUEING BRACKET SET *

Aluminium glueing bracket for LSG and glass clamping plate 30

Designation	Description	Ident-No.
LSG glueing bracket set *	for use with LSG in connection with glass clamping plate 30 mm, for 2 clamping plates, without adhesive	142386

DOOR PULL HANDLE, CONFIGURED *

Push bar - round design for installation on glass leaves

Designation	Ident-No.	Colour
Door pull handle, configured *	127616	Stainless steel

PERLAN SOFTSTOP SET, SHORT VERSION, DAMPED ON ONE SIDE, UP TO 80 KG

Perlan SoftStop damping on one side for leaf weights up to 80 kg and leaf widths of 575 to 900 mm

Designation	Description	ldent- No.	Leaf width (min.)	Leaf width (max.)
Perlan SoftStop set, short, one side	The set includes: 2 x roller carriage with damping unit on one side, 2 x end stop, 1 x trigger with fixing screw, 2 x standard suspension plate	128876	575 mm	900 mm





2 2









FLOOR GUIDE SET GLASS GUIDE

Floor guide for glass sliding leaves for glass thickness 8, 10 and 12 mm



Designation	Description	Ident-No.	Colour	Glass thickness
Floor guide for glass leaf (stainless steel)	For 8, 10, 12 mm glass	134990	Stainless steel	8 – 12 mm

COMPLETE CLIP-ON COVER SET 100

Clip-on cover for covering Perlan door fitting systems



Designation	Description	Ident-No.	Type of installation
Complete clip-on cover set 100	for wall and ceiling mounting, continuous cover, bespoke configuration	138098	Wall, Ceiling

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.